



CASE STUDY OF TRANSPORT OPTIONS FOR CO₂ FROM IGCC COAL POWER PLANT IN THE CZECH REPUBLIC FOR STORAGE

Vesely L., Skaugen G., Vitvarova M., Roussanaly S., Novotny V.,
Czech Technical University in Prague, Faculty of Mechanical
Engineering,
SINTEF Energy Research, Trondheim, Norway

Mikulov, 26. 4. 2016



Outline

- Introduction
- Description of transport method
- Description of transport route
 - On-shore
 - Off-shore
- Description of calculation
- Input parameters
- Result
- Conclusion



Introduction



- Case study of several options for CO₂ transport from an Integrated Gasification Combined Cycle (IGCC) power plant with integrated CCS.
- The modelled case input comes from a hypothetical IGCC plant fuelled with lignite and using solvent pre-combustion capture method (Rectisol) located in the Czech Republic.
- Case study:
 - Hypothetical IGCC plant – located near the Power plant Prunéřov
 - Production of CO₂ mixtures 54 kg/s



Description of transport method



- Transportation can be performed for the two phases of CO₂.
 - liquid phase
 - gas phase
- The suitable transport type is selected in depending on the phase.
- Two ways of transport.
 - Transport via pipelines:
 - Transport of CO₂ in the gas phase in a region above the critical pressure.
 - Operating pressure - 8.6 to 20 MPa
 - Operating temperature - 4 °C to 38 °C
 - Transport of CO₂ in the pressurized container:
 - Transport is performed by ships, trucks or trains.
 - The transport pressure for liquid CO₂ is in the range from 0.52 MPa up to 7.3 MPa and temperature is about -50 °C.



Description of transport method



- Recommended composition of mixtures for the transport of CO₂:



Description of transport route



- The storage is considered in two locations:
 - on-shore
 - off-shore
- On-shore storage is located in the Zatec basin.
 - Transport via pipeline is length about 23 km.
- In case of transport in the liquid phase are selected two routes for on-shore storage.
 - Transport in the liquid phase is considered using trains.
 - The length of the transport routes is about 50 km for both route.



On-shore

- The pipeline b) The train for on-shore




- Elevation for transport via pipeline (on-shore)



Off-shore

- Transport of CO₂ to off-shore locations is taken into account also in liquid and gaseous phase.
- The route is approximately 120 km from pipeline to the EU CCS continental pipe.
 - The route is via mountains.
- The total length of the pipeline is about 500 km from power plant to off-shore storage (North Sea coast).




Description of calculation

- The calculation is performed for transport via pipeline.
 - The CO₂ feed temperature and pressure is -15°C at atmospheric pressure.
 - The pipeline transport initial pressure is 150 bar.
- During the conditioning and compression any water present in the CO₂ stream is removed as liquid in the separators prior to each compression stage.
 - The water has already been removed in the capture process and the compression is taken place in the single phase gas region.



Description of calculation

- The Compression process.




Legend:

P Pressure (bar)

T Temperature (°C)

Pressure-enthalpy diagram with isotherms and compression route



Description of calculation

- The calculation of the energy consumption for the pipeline is done calculating the local frictional pressure loss based on the varying fluid temperature and pressure along the pipeline.
 - An average ambient temperature of 15°C is used with the pipeline buried at 1.0 m depth in soils with a thermal conductivity of 2.4 W/m K.
- The minimum pressure of 90 bar in the pipeline is defined and for both the on-shore (23 km) and off-shore (120 km) case.
 - The dimensions of the pipeline are taken out of the norm ASME B31.4-2002.



Description of calculation

- The parameters for calculation of transport of CO₂.



Result

- The Result for the compression station and pipeline for on-shore and off-shore.
- Total power will be increased if will be need next booster station.
 - In this case is not necessary use other booster station.



Result – on-shore

- Impact of elevation on temperature in pipeline – on-shore.
- Impact of elevation on pressure in pipeline – on-shore.



Result – off-shore

- Impact of elevation on temperature in pipeline – off-shore.
- Impact of elevation on pressure in pipeline – off-shore.



Conclusion

- On-shore:
 - Pressure drop – 2.85 bar
- Off-shore
 - Pressure drop – 20.05 bar
- Outlet temperature
- In this case is not necessary use other booster station

Future work:

- The next step is the calculation of transport in liquid phase for on-shore and off-shore.
- The calculation of transport via pipeline with different dimension of pipe.
- Further, it will carry out an economic analysis of modes of transport, taking into account the construction of a new pipeline or a new railway connections.



Thank you for your
attention

